

# Carpet Cover™

Fire Retardant Carpet Cover™ and Carpet Cover™ are temporary carpet protection films featuring a pressure sensitive water-based adhesive system designed specifically for carpet.

# Carpet Cover™

Available  
in FR

## FEATURES, ATTRIBUTES AND BENEFITS:

- ★ Provides outstanding protection for any carpeted surface
- ★ High quality 3 mil clear *specialty* film outperforms similar LDPE based products
- ★ Clean release for easy removal **without adhesive transfer**
- ★ Amazingly strong, durable, puncture and tear resistant
- ★ High Tech, water-based adhesive system has major benefits over solvent-based systems
- ★ Will not discolor or dye carpets
- ★ All dirt, dust and debris can be rolled into or folded into film, leaving carpet clean
- ★ Designed for jobs, events, or projects up to 45 days per application
- ★ 100% made in the U.S.A.

## FIRE RETARDANT FEATURES, ATTRIBUTES AND BENEFITS:

CCFR is the first original known self-adhesive fire retardant carpet protection film. Developed by Americover®.

- ★ Flame Retardant version of Carpet Cover™ has the added feature of increased fire safety for applications where this is required or provides additional benefit
- ★ Specified for use on many maritime, government, school and hospital projects
- ★ Passes NFPA 701-04 Test 1 Fire Retardant Standard (vertical test accepted worldwide)
- ★ Passes CFR 1630 Fire Retardant Standard (used to certify fire retardant carpeting)
- ★ Film is translucent eggshell color
- ★ Saves time and money



Carpet Cover™ being rolled out



Carpet Cover™ FR and Applicator



Carpet Cover™ FR Fully Applied

# Americover®

## CARPET COVER™

- ★ These 3 mil clear polyethylene films are wound with the adhesive side out so it quickly and easily rolls onto carpet
- ★ Fire Retardant Film increases fire safety on the jobsite!
- ★ Ideal carpet protection during construction, homebuilding, remodeling, tenant improvement, demolition, repairing, maintenance, drydocks, parties, events, open houses, move-in/move-outs and restorations
- ★ Stocked in our most popular sizes in multiple locations
- ★ Special versions stocked for automotive, RV, cruise lines, convention and wool carpet applications



## Easy Product Integration

### EASY CLEANUP

#### TECHNICAL INFO

Manufactured in an ISO 9002-2000 certified facility

Applicators available

Apply to dry carpet.

Elongation factor in the:

Transverse Direction = 850%

Machine Direction = 680%

Tensile Strength in the:

Transverse Direction = 3500 psi

Machine Direction = 4200 psi

#### DISCLAIMER

**Please note:** The highly aggressive adhesive on Carpet Cover™ is designed for use on carpet only. We recommend complete coverage of carpeted areas.

