



**Americover PSR 6BW**  
**6 mil Black/White**  
**String Reinforced Film**

| <b>PROPERTIES</b>           | <b>TEST METHOD</b>        | <b>Americover PS R6BW</b>                        |
|-----------------------------|---------------------------|--|
| APPEARANCE                  |                           | BLACK/WHITE                                      |
| WEIGHT PER MSF              |                           | 29 LBS   |
| THICKNESS (NOMINAL)         |                           | 6 MIL  |
| ELONGATION @ MAX LOAD %     |                           |  |
| DIAGONAL A                  | ASTM D7003                | 595 %  |
| DIAGONAL B                  |                           | 598 %  |
| GRAB TENSILE                |                           |  |
| DIAGONAL A                  | ASTM D7004                | 66 LBS   |
| DIAGONAL B                  |                           | 67 LBS   |
| TRAPEZOIDAL TEAR            |                           |  |
| DIAGONAL A                  | ASTM D4533                | 51 LBS   |
| DIAGONAL B                  |                           | 48 LBS   |
| HYDROSTATIC RESISTANCE      | ASTM D751,<br>PROCEDURE A | 45 PSI   |
| WATER VAPOR<br>TRANSMISSION | ASTM E96                  | 0.421 g/day/m2<br>0.170 g/hour/m2<br>0.069 Perms |

NOTE: TEST RESULTS WERE COMPILED BY AN INDEPENDENT LABORATORY. RESULTS LISTED ARE THE MEAN RESULTS OF THESE TESTS.

AMERICOVER® PSR 6BW IS A BLACK/WHITE REINFORCED STRING MATERIAL. THIS MATERIAL IS MANUFACTURED BY PLACING A WEB OF 1,000 DENIER STRING BETWEEN TWO LAYERS OF HIGH STRENGTH POLYTHEYLENE AND THEN LAMINATING THE MATERIAL TOGETHER WITH MOLTEN POLYETHYLENE.

*Covering You From The Ground Up*

2067 Wineridge Place, Ste. F • Escondido, CA 92029 • 800-747-6095 • 760-747-6095 • fax 760-747-1920

[www.americover.com](http://www.americover.com)