

8 Mil Black Plastic

Material Safety Data Sheet

SECTION I

MANUFACTURER'S NAME

Americover Inc

EMERGENCY TELEPHONE NO.

800-747-6095

ADDRESS (Number, Street, City, State and Zip Code)

2067 Wineridge Pl., Ste. F Escondido, CA 92029

PRODUCT IDENTIFICATION

Fire Retardant 8 mil black polyethylene

USE/DESCRIPTION

Protective Plastic Sheeting

DATE OF MOST RECENT REVISION

2/27/06

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS

CAS NO.

ACGIH-TLV

ACGIH - STEL

%

Not Applicable

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT

N/A

SPECIFIC GRAVITY (H₂O = 1)

.910-.925

VAPOR PRESSURE (mm Hg.)
(at 77°F)

N/A

MELTING POINT

VAPOR DENSITY (AIR = 1)

N/A

EVAPORATION RATE (Butyl Acetate = 1)

N/A

SOLUBILITY IN WATER

N/A

APPEARANCE AND ODOR

Black polyethylene film 4 mils thick - no odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used)

N/A

FLAMMABLE LIMITS

N/A

LEL

UEL

EXTINGUISHING MEDIA

Water spray, dry chemical, CO₂

SPECIAL FIRE FIGHTING PROCEDURES

Self contained breathing apparatus and protective clothing should be worn in fighting fire involving chemicals

UNUSUAL FIRE AND EXPLOSION HAZARDS

None

PAGE (1)

Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control. All risks of use of the product are therefore assumed by the user and we expressly **disclaim all warranties of every kind and nature**, including **warranties of merchantability and fitness for a particular purpose in respect to the use or suitability of the product**. Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and sale handling procedures should be provided to handlers and users.

SECTION V - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	XX	
INCOMPATIBILITY (Materials to avoid) Oxidizing materials can cause a reaction			
HAZARDOUS DECOMPOSITION OR BYPRODUCTS As with other organic materials, combustion will produce carbon dioxide and probably carbon monoxide.			
HAZARDOUS POLYMERIZATION			CONDITIONS TO AVOID
	Will not occur		

SECTION VI - HEALTH HAZARD DATA

HEALTH HAZARDS			
CARCINOGENICITY	NTP?	IARC MONOGRAPHS?	OSHA REGULATED?
SIGNS AND SYMPTOMS OF OVEREXPOSURE N/A			
EMERGENCY AND FIRST AID PROCEDURES			
EYES:	SKIN:	SWALLOWED:	
If burned by contact with hot plastic, cool molten material adhering to the skin as quickly as possible with cold water. See A physician for removal of the adhering material and treatment of the burn.			

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED N/A
WASTE DISPOSAL METHOD Incineration or landfill. Observe all federal, state and local regulations regarding disposal.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

SECTION VIII - CONTROL MEASURES: For Use Where Significant Eye, Skin Or Inhalation Exposure Is Likely

RESPIRATORY PROTECTION (Specify Type)		
VENTILATION	LOCAL EXHAUST N/A	SPECIAL N/A
	MECHANICAL (General) N/A	OTHER N/A
PROTECTIVE GLOVES N/A	EYE PROTECTION N/A	
OTHER PROTECTIVE CLOTHING OR EQUIPMENT N/A		
WORK/HYGIENIC PRACTICES		