

HSW 12

# Material Safety Data Sheet

## SECTION I

MANUFACTURER'S NAME <b>Americover Inc</b>		EMERGENCY TELEPHONE NO. <b>800-747-6095</b>
ADDRESS (Number, Street, City, State and Zip Code) <b>2067 Wineridge Pl., Ste. F Escondido, CA 92029</b>		
PRODUCT IDENTIFICATION <b>Fire Retardant 12 mil white polyethylene</b>	USE/DESCRIPTION <b>Protective Plastic Sheeting Heat shrinkable</b>	DATE OF MOST RECENT REVISION <b>6/1/11</b>

## SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS	CAS NO.	ACGIH-TLV	ACGIH - STEL	%
Not Applicable				

## SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT	N/A	SPECIFIC GRAVITY (H <sub>2</sub> O = 1)	.910-.925
VAPOR PRESSURE (mm Hg.) (at 77°F)	N/A	MELTING POINT	225°
VAPOR DENSITY (AIR = 1)	N/A	EVAPORATION RATE (Butyl Acetate = 1)	N/A
SOLUBILITY IN WATER N/A			
APPEARANCE AND ODOR White polyethylene film 12 mils thick - no odor			

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used) N/A	FLAMMABLE LIMITS N/A	LEL	UEL
EXTINGUISHING MEDIA Water spray, dry chemical, CO <sub>2</sub>			
SPECIAL FIRE FIGHTING PROCEDURES Self contained breathing apparatus and protective clothing should be worn in fighting fire involving chemicals			
UNUSUAL FIRE AND EXPLOSION HAZARDS None			

PAGE (1)

Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control. All risks of use of the product are therefore assumed by the user and we expressly disclaim all warranties of every kind and nature, including warranties of merchantability and fitness for a particular purpose in respect to the use or suitability of the product. Nothing is intended as a

recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and sale handling procedures should be provided to handlers and users.

## SECTION V - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	XX	Extreme temperatures over 572°F
INCOMPATIBILITY (Materials to avoid)			
HAZARDOUS DECOMPOSITION OR BYPRODUCTS			
As with other organic materials, combustion will produce carbon dioxide and probably carbon monoxide over 572°F.			
HAZARDOUS POLYMERIZATION			CONDITIONS TO AVOID
	Will not occur		

## SECTION VI - HEALTH HAZARD DATA

HEALTH HAZARDS			
CARCINOGENICITY	NTP?	IARC MONOGRAPHS?	OSHA REGULATED?
	no	no	no
SIGNS AND SYMPTOMS OF OVEREXPOSURE			
N/A			
EMERGENCY AND FIRST AID PROCEDURES			
EYES:	SKIN:	SWALLOWED:	
If burned by contact with hot plastic, cool molten material adhering to the skin as quickly as possible with cold water. See a physician for removal of the adhering material and treatment of the burn.			

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Sweep up and discard
WASTE DISPOSAL METHOD
Incineration or landfill. Observe all federal, state and local regulations regarding disposal.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Reasonable care when handling

## SECTION VIII – CONTROL MEASURES: For Use Where Significant Eye, Skin Or Inhalation Exposure Is Likely

RESPIRATORY PROTECTION (Specify Type)		
Not needed		
VENTILATION	LOCAL EXHAUST N/A	SPECIAL N/A
	MECHANICAL (General) N/A	OTHER N/A
PROTECTIVE GLOVES	EYE PROTECTION	
N/A	N/A	
OTHER PROTECTIVE CLOTHING OR EQUIPMENT		
N/A		
WORK/HYGIENIC PRACTICES		

