

223DT TAPE

WHITE DUCT TAPE



PRODUCT

223 White Duct Tape

PART NUMBER

223DT

APPLICATIONS

- Hanging and seaming poly sheeting
- Sealing and closure tape for poly bags
- Color coding
- Temporary holding and bundling
- General purpose packaging
- Sealing duct work
- Aerospace industry

PRODUCT DESCRIPTION

PE-coated cloth backed duct tape with a natural rubber based adhesive that offers a good balance of tensile strength and tearability. Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®.

Versatile performance. Good tensile strength. Good adhesion and tack. Conformable and will not twist or curl during application. Low residue.

Color: White

SIZE & PACKAGING

Standard sizes:
48mm X 55m, 72mm X 55m

Recommended Storage Conditions:
32-90 °F at 50% RH +/- 2%

Standard Shelf Life (at 25 °C):
36 months from date of manufacture

223DT TAPE

WHITE DUCT TAPE

PROPERTIES	TEST	IMPERIAL VALUES	METRIC VALUES
Adhesion to Steel	PSTC-101	90 oz/in	9.85 N/cm
Adhesion to Backing	PSTC-101	40 oz/in	4.38 N/cm
Tensile Strength	ASTM D1000	27 lb/in	47.28 N/cm
Thickness	ASTM D1000	10 mil	0.254 mm
Elongation	ASTM D1000	24%	24%
Operating Temperature	-	40° - 200° F	4° - 93° C
VOC Content	-	<1g/L	-



The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, express or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

Scan for our mobile app

