

BLACK FR 4 & 8 MIL POLY

BLACK FIRE RETARDANT POLYETHYLENE SHEETING



PRODUCT

4 mil Black FR	B4
8 mil Black FR	B8

PART NUMBER

APPLICATIONS

- Cargo covers
- Black-out curtains
- Covering sensitive shipments
- Creating barrier walls or divisions
- Covering any surface requiring fire retardant film

PRODUCT DESCRIPTION

- Certified to pass: NFPA 701-2004 test 1
- Certified to pass: California Title 19 Fire Retardant Standard
- 4 mil available in roll sizes : 10' x 100' & 20' x 100'
- 8 mil available in roll sizes: 5' x 500' & 24' x 100'
- Tested and approved for the Boeing BAC5034-2 and PSD 6-19
- Creates excellent protection for many types of jobs
- Tapes easily in place; easy to cut and size around permanent objects
- Protects against spill and moisture

SIZE & PACKAGING

10'X100' & 20'X100' rolls available

BLACK FR 4 & 8 MIL POLY

BLACK FIRE RETARDANT POLYETHYLENE SHEETING

PROPERTIES	TEST DIRECTION	TYPICAL VALUES	UNITS
Tensile Elongation	Machine Direction	525	%
Tensile Elongation	Transverse Direction	650	%
Tensile Strength	Machine Direction	2500	psi
Tensile Strength	Transverse Direction	2300	psi
Elmendorf Tear Strength	Machine Direction	1.25	lbf
Elmendorf Tear Strength	Transverse Direction	2.5	lbf



The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, express or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

Scan for our mobile app

