

CARPET COVER FR

FIRE RETARDANT CARPET COVER



PRODUCT DESCRIPTION

A durable polyolefin film that is coated with a blend of premium water based adhesive polymers. The result is an aggressive masking that is an excellent choice for carpet protection and various other masking applications that require high peel and quick grab. Americover's carpet masking can be used on those hard to adhere materials including highly textured plastics, coarse fabrics and other demanding applications. As with all Americover products, it provides outstanding protection. (This product has also performed well on many other substrates not listed and needs to be fully tested and approved for compatibility to the substrate being masked.)

PRODUCT

PART NUMBER

Fire Retardant Carpet CoverCCFR

PRODUCT USE

It is recommended that all products be stored and applied indoors at room temperature 60° - 80° F (16° - 27° C) and that relative humidity levels be kept between 30% - 70%. All products should be rotated so the "first-in, first-out" inventory method is utilized. For best results products should be applied to a clean, dry surface.

The data listed above reflects the average values obtained in testing. Various other environmental conditions will vary the end user's actual results - temperature at time of application, pressure of lamination, surface material to be masked (glossy, matte or textured) and humidity. It is best for the purchaser to test the suitability of our products under their unique conditions.

APPLICATIONS

- Carpet Covers for high-volume traffic

CARPET COVER FR

FIRE RETARDANT CARPET COVER

PROPERTIES	TEST METHOD	VALUES
Film Backing	-	Low Density Polyethylene (LDPE)
Gauge	ASTM D3652	3.0 mil (0.003")
Tensile Strength	ASTM D882	3200 psi (md)
Elongation at Break	ASTM D882	500% (md)
Adhesion (oz/inch at 180°)	Modified PSTC #1	30.0
Adhesive Color	-	Water Clear



The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, express or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

Scan for our mobile app

