

VAPOR TAPE

RUBBER ADHESIVE POLYETHYLENE TAPE



PRODUCT

PART NUMBER

Vapor TapeVTW

APPLICATIONS

- Seaming or mending Crawlspace Encapsulations
- Seaming or mending Vapor Barriers

PRODUCT DESCRIPTION

Backing: Polyethylene Film

Adhesive: Rubber

Liner: N/A

Colors: White

Specifications: Meets DPM #871-2, #871-3& #877-1

Standard Sizes: 4" x 180'

- Polyethylene Film Backing
- Natural rubber based adhesive
- Low VOC Content
- Conformable and flexible
- Excellent durability & solvent resistance
- Withstands outdoor exposure and moisture
- High tack for a secure bond
- Repositionable & clean removal - no residue
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

PRODUCT USE

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F Standard

Shelf Life (at 25°C): 24 months from date of manufacture

SIZE & PACKAGING

Standard Sizes: 4" x 180'

VAPORTAPE

RUBBER ADHESIVE POLYETHYLENE TAPE

PROPERTIES	TEST METHOD	IMPERIAL	METRIC
Total Thickness	ASTM D1000	8 mil	203.2 mic
Adhesion to Steel 60	PSTC 101	60 oz/in	6.57 N/cm
Tensile Strength	ASTM D1000	21 lb/in	36.78 N/cm
Operating Temperature	-	40° to 200°F	4° to 93°C
MVTR (96% RH, 100°F)	ASTM D3833	0.112 perms	-
VOC Content	-	<2 g/L	-
Elongation	-	70%	-

The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, express or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

Americover[®]

Scan for our mobile app



PROTECTION FROM THE GROUND UP

2067 Wineridge Place, Suite. F
Escondido, CA 92029