


# STEELE TAPE™ 787-20B

BLACK FLAME RETARDANT PVC TAPE



## PRODUCT DESCRIPTION

STEELE TAPE™ 787-20B is designed to resist the attack of oil, chemicals, solvents, acids, moisture, and corrosion as well as excellent resistance to high voltage.

It is ideal for electrical binding, application to carbon composite and CFRP.

Roll Size: 3" x 60'

PROPERTIES	TEST	IMPERIAL VALUES	METRIC VALUES
Total Thickness	-	5.0 mils	0.127 mm
Tensile Strength	ASTM D1000	17 lbs/in	272 oz/in
Elongation	ASTM D1000	220%	220%
Adhesion to Steel	ASTM D1000	Max 18 oz/in Min 22 oz/in	Max 18 oz/in Min 22 oz/in
Dielectric	ASTM D1000	8,000 volts	8,000 volts
Temp/Range	ASTM D1000	32°F-177°F	0°C-80.5°C
Color	-	Black	

The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, express or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

\*ALL DATA IS DRAWN FROM U.S. TESTING AND PRECISION LABORATORIES. AVAILABLE UPON REQUEST.

TT.060717.082718