



# CORREX<sup>®</sup> BOARD

FLAME RETARDANT PROTECTION



## PRODUCT DESCRIPTION

Americover has partnered with Temprotech as their United States distribution partner. Temprotech provides flame retardant protection products that meet the exacting demands of the shipbuilding, ship repair and offshore markets.

## APPLICATIONS

- ▶ Cruise ship/Dry Dock Area
- ▶ Shipyards
- ▶ Ship Repair
- ▶ Offshore Markets
- ▶ Temporary Protection for floors, walls, doors and horizontal surfaces

## PRODUCT USE

Protecting floors, surfaces or equipment and maintaining clean work environments are essential to the successful progress and completion of new building or installation projects and during periods of maintenance, repair or refurbishment.

Flame retardant protection materials can reduce dirt, spillages overspray and accidental damage, and eliminate fire hazards for a safer work environment, saving time and money on cleanup replacement and repairs before handover.

Brand leading Correx<sup>®</sup> Board is extruded from flame retardant polypropylene into a wide range of weights, grades and custom sizes of fluted board.

It provides an extremely versatile form of protection offering light through to heavy duty compression and impact resistance for floors, walls, doors and horizontal surfaces. Correx<sup>®</sup> is light, clean, easy to work with and can be re-used, giving a cost effective alternative to traditional wood products.

## PART NUMBERS

#TPT3270BS

#TPT3350BS

#TPT38700BS



800.747.6095  
760.747.6095



Inquiries@americover.com  
www.americover.com



2067 Wineridge Place, Suite F · Escondido, CA 92029



# CORREX<sup>®</sup> BOARD

## SPECIFICATIONS

| CAPABILITY        |   | STANDARD ITEMS                         |  |  |
|-------------------|---|--|--|--|
| Part #            |   | TPT3270BS                              | TPT3350BS                              | TPT38700BS                             |
| Thickness         | 2.00mm - 4.0 mm                             | 2.33 mm                                | 2.6 mm                                 | 4.0 mm                                 |
| Density           | 250 g/m <sup>2</sup> - 700 g/m <sup>2</sup> | 270 g/m <sup>2</sup>                   | 350 g/m <sup>2</sup>                   | 700 g/m <sup>2</sup>                   |
| Sheet Width       |   | 1.0m or 1.22 m                         | 1.0 m or 1.22 mm                       | 1.0 m or 1.22 m                        |
| Sheet Length      |   | 2.0 or 2.44 m                          | 2.0 m or 2.44 m                        | 2.0 m or 2.44 m                        |
| Sheet Area        |   | 2.0m <sup>2</sup> or 3.0m <sup>2</sup> | 2.0m <sup>2</sup> or 3.0m <sup>2</sup> | 2.0m <sup>2</sup> or 3.0m <sup>2</sup> |
| Sheet Weight      |   | 0.54 kg or 0.81 kg                     | 0.70 kg or 1.05 kg                     | 1.40 kg or 2.10 kg                     |
| Sheets per Pallet |   | 500                                    | 333                                    | 250                                    |
| Color             |   | White                                  |  |  |
| Approvals         | LPS1207 Cert. 227a                          | LPS1207 Cert. 227a<br>French Norms M2  | LPS1207 Cert. 227a                     | LPS1207 Cert. 227a<br>NFPA701          |

**NOTE:** To the best of our knowledge, unless otherwise stated, these are typical property values and are intended as guides only, not as specification limits. Chemical resistance, odor transmission, longevity as well as other performance criteria is not implied or given and actual testing must be performed for applicability in specific applications and/or conditions. AMERICOVER, INC. MAKES NO WARRANTIES AS TO THE FITNESS FOR A SPECIFIC USE OR MERCHANTABILITY OF PRODUCTS REFERRED TO, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability for resulting loss or damage. Limited Warranty available at [www.Americover.com](http://www.Americover.com)

TT04.10.19