



225FR Fire Retardant Tape

WHITE PRINTED FLAME RETARDANT CLOTH TAPE



PRODUCT DESCRIPTION

The 225FR White Fire Retardant Tape features a PE-coated cloth backing and natural rubber adhesive for strong, long-lasting adhesion. With a 12-mil thickness, it resists moisture, solvents, and abrasion, while offering easy handling and clean application. Designed for durability and flame resistance in demanding environments and conforms to:

- ▶ FAA specification FAR 25.853(a)
- ▶ McDonnell-Douglas spec DMS 1986D
- ▶ Lockheed spec LCP-86-1226-A
- ▶ Boeing spec D 6-8099

APPLICATIONS

- ▶ Duct Systems
 - ▶ Wire Harnessing
 - ▶ Wire Bundling
 - ▶ Overlapping Plastic Sheeting
- Panels

PRODUCT USE

225FR White Fire Retardant Tape is ideal for sealing, patching, and bundling in environments where flame resistance is critical, such as aircraft cargo areas and industrial settings. For best performance, apply to surfaces that are clean and free of dirt, dust, and debris to ensure a strong, reliable seal.

SIZE AND PACKAGING

Sold in individual rolls of 2" x 180' or 3" x 180'

PROPERTIES	TEST METHOD	IMPERIAL VALUES	METRIC VALUES
60 second vertical burn drip	FAR 25.853(a)	No Drip	N/A
60 second vertical burn length		5 in	12.7 cm
60 second vertical burn time		0.5 sec	N/A
Adhesion to Backing	PSTC-101	41 oz/in	45.9 g/mm
Adhesion to Steel		66 oz/in	72 g/mm
Tack	ASTM D1000	2.5 in	6.35 cm
Tensile Strength		26 lb/in	0.46 kg/mm
Thickness		12 mil	0.3mm
Weight		10.5 oz/sq yd	356 g/m2

The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, express or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

BG.070815.04092025