



WOVEN COATED POLY

12 MIL CLEAR WOVEN POLYETHYLENE



PRODUCT DESCRIPTION

12 Mil Clear Woven Polyethylene. Utilized for topping large, wind and heat sensitive areas. Its non-stretch fabric is the perfect material for grain storage, landfills, soil piles and rain protection. Allowing 80% UV transfer. This material is fabricated to custom sizes.

*ALL DATA IS DRAWN FROM U.S. TESTING AND PRECISION LABORATORIES. AVAILABLE UPON REQUEST.

PROPERTIES	Test Method	VALUES
Weight	-	6.0 oz/sq yd (+/-10%)
Thickness	-	12 Mil (+/-10%)
Tensile Strength (grab method)	ASTM D 5034*	Warp 220 lbs Weft 175 lbs
Tear Strength (tongue method)	ASTM D 4533*	Warp 65 lbs/in Weft 65 lbs/in
Light Transmittance	ASTM G-151*	Visible 80%

NOTE: To the best of our knowledge, unless otherwise stated, these are typical property values and are intended as guides only, not as specification limits. Chemical resistance, odor transmission, longevity as well as other performance criteria is not implied or given and actual testing must be performed for applicability in specific applications and/or conditions. AMERICOVER, INC. MAKES NO WARRANTIES AS TO THE FITNESS FOR A SPECIFIC USE OR MERCHANTABILITY OF PRODUCTS REFERRED TO, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability for resulting loss or damage. Limited Warranty available at www.Americover.com

B.042017.061917