



ASFR6

6 MIL WHITE ANTI-STATIC, FIRE RETARDANT POLY SHEETING



PRODUCT DESCRIPTION

ASFR6 is a 6 mil, fire retardant, anti-static film. This specialized plastic sheeting was originally designed to meet the regulations of the telecommunications industry. Therefore, it conforms to regulations dated October 1, 2001, Section B, TP 76300MP 1.2.7: "All combustible materials stored overnight in the equipment area shall be completely covered with a fire retardant tarp that meets the NFPA 701 or U L214 and is clearly marked as such".

APPLICATIONS

- ▶ Enclosure film for Hospitals and schools
- ▶ Cargo covers
- ▶ Black-out curtains
- ▶ Covering sensitive shipments
- ▶ Creating barrier walls or divisions
- ▶ Covering any surface requiring fire retardant film

PRODUCT USE

This 6 mil polyethylene film is printed with the fire retardant standard and is suitable for indoor and outdoor use. It can be used to cover a variety of surfaces including electronic equipment. It also prevents static electricity buildup.

SIZE AND PACKAGING

PART NUM	ROLL SIZE	PART NUM	ROLL SIZE
ASFR612	12' x 100'	ASFR620	20' X 100'

PROPERTIES	TEST METHOD	VALUES
Thickness		6 mil
Tear Strength	ASTM D1922	Machine Direction: 1,000 grams Transverse Direction: 2,000 grams
Tensile Strength	ASTM D882	Machine Direction: 3,000 psi Transverse Direction: 3,000 psi
Ultimate Elongation	ASTM D882	Machine Direction: 600 Transverse Direction: 600
Dart Impact	ASTM D1709	400 grams
Surface Resistivity	ANSI/E05/ESD-S11.11	10 ¹² max ohms/sq
Flammability	NFPA 701	Pass
Melt Index		180 degrees fahrenheit

NOTE: The data presented above are nominal values for the product type described based on random tests performed at the time of manufacture, and should not be considered as limiting specifications. There is no guaranty expressed or implied regarding the use of this information or its suitability for a particular application.

OE.062117.06032025



800.747.6095
760.747.6095



Inquiries@americover.com
www.americover.com



2067 Wineridge Place, Suite F • Escondido, CA 92029

