

Specialty Construction Tapes Line Card



Tape	225FR	268FR	377FRPE	Steele Tape	Griff Tape FR	Reinforced Repair Tape (PST)	Heat Shrink Tape	White Felt Tape	Black Vapor Seaming Tape (R25B)
Description	Flame Retardant Polyethylene Coated Cloth Tape	Flame Retardant Acrylic Coated Cloth Tape	Flame Retardant Polyethylene Tape	Flame Retardant PVC Tape	Flame Retardant Industrial Cloth Tape	String Reinforced Polyethylene Tape	Polyethylene Tape	Felt Tape	Multi Polymer Tape
Feature	Fire Retardant	Fire Retardant	Fire Retardant	Fire Retardant	Fire Retardant	UV Resistant	UV Resistant	UV Resistant	UV Resistant, Vapor Resistant
Thickness	12 Mil	8.5 Mil	7.2 Mil	5 Mil	11 mil	20 Mil	9 Mil	3.175 mm	8 Mil
Color	White/Printed	Black	Blue	Black	White	Clear, White, Black	Clear, Blue, White	White	Black
Sizes	2", 3" x 180'	2" x 100'	4" x 180'	3" X 60'	4" x 180'	4" x 50'	2", 3", 4", 6" x 180'	2", 3", 4" x 180'	4" x 100'
Operating Temperature Range	40°F to 200 °F	20°F to 221 °F	20°F to 200 °F	32°F to 177 °F	50 F and above	50 F and above	32°F to 160 °F	32°F to 160 °F	-20°F to 180 °F
Adhesive Base	Rubber	Rubber	Rubber	Rubber	NA	Rubber	Rubber	Rubber	Synthetic Elastomeric
Tack Type	Aggressive	Aggressive	Pressure Sensitive	Aggressive	Aggressive	Pressure Sensitive	Pressure Sensitive	Pressure Sensitive	Aggressive
Adhesion to steel	66 oz/in	60 oz/in	75 oz/in	22 oz/in	40 oz/in	NA	70 oz/in	60 oz/in	144 oz/in
Removes Easily	Yes	Yes	Yes	Yes	No	Initially	No	Initially	No

Specialty Construction Tapes Line Card



Tape	White Vapor Seaming Tape (VTW)	Black Double Sided Butyl Tape	DST - 2 Sided Clear Tape	VaporBond Tape	TBOOT Stretchable Butyl Tape	VaporSeal Tape	Griff Tape	Permalon Pressure Sensitive Tapes
Description	Polyethylene Tape	Double-Coated Reinforced Butyl Tape	Double-Coated Seaming Tape	Polyethylene Tape	EPDM Tape	EVOH/LLDPE Tape	Industrial Cloth Tape	Polyethylene Tape
Feature	Vapor Resistant	Vapor Resistant	Vapor Resistant	Vapor Resistant	Vapor Resistant	Vapor Resistant	Vapor Resistant	Vapor Resistant/ moisture
Thickness	6.7 Mil	35 Mil	15.9 Mil	6.7 Mil	20 Mil	7 Mil	11 Mil	30.5 Mil
Color	White	Black	Clear	White	Black	Silver	White, Black	Black
Sizes	4" x 210'	1.5" x 300'	1.5" x 300'	4" x 210'	2" x 16.4'	4" x 160' 12" x 50'	4" x 180'	4" x 50'
Operating Temperature Range	-40°F to 200 °F	-30°F to 200 °F	0°F to 140 °F	-40°F to 180 °F	14°F to 122 °F	-40°F to 190 °F	50 F and above	32°F to 200 °F
Adhesive Base	Rubber	Butyl Rubber	Rubber	Butyl Rubber	Butyl Rubber	Acrylic	NA	NA
Tack Type	Pressure Sensitive	Aggressive	Aggressive	Pressure Sensitive	Aggressive	Pressure Sensitive	Aggressive	Permanent
Adhesion to steel	35 oz/in	40 oz/in	150 oz/in	35 oz/in	145 oz/in	80 oz/in	38 oz/in	NA
Removes Easily	Initially	No	No	Initially	No	Initially	No	Initially