



# BUTYL TAPE

BLACK DOUBLE-SIDED BUTYL RUBBER TAPE



## PRODUCT DESCRIPTION

The 20 mil thick butyl adhesive contains a lightweight reinforcement that prevents the tape from stretching or “necking” when being applied. The tape is applied with the release liner still adhered to the reverse side and is removed just prior to applying the overlapped layer of material.

## APPLICATIONS

- ▶ Under slab
- ▶ Walls & roofs
- ▶ Crawl spaces
- ▶ Landfills
- ▶ Ponds

## PRODUCT USE

The tape will not adhere to dirty or wet surfaces. The application area should be completely cleaned and dry. Accumulations of dust should also be removed to insure a secure seam. Optimum adhesion occurs when the application surface is above 50-60°F. In order to obtain a bond at lower temperatures, external heat may be required. Extra care should be taken when attempting to install tape at temperatures below 32°F.

## SIZE AND PACKAGING

Sold in individual rolls of 1.5” x 300’.

| PROPERTIES                    | U.S. VALUE  | METRIC VALUE |
|-------------------------------|-------------|--------------|
| Thickness                     | 35 Mils     | .9 MM        |
| Width                         | 1.5 In.     | 38 MM        |
| Roll Length                   | 100 Ft.     | 30.5 M       |
| Roll Weight                   | 3.75 LBS    | 1.7 KG       |
| Specific Gravity              | 1.4         | 1.4          |
| Solubility in Water           | Insoluble   | Insoluble    |
| T-55 Black 3” Peel            | 19 LBS      | 84.5 N       |
| TX-1200 Black 3” Shear        | 31 LBS      | 138 N        |
| Temperature for Testing Above | 50° - 95° F | 10° - 35° C  |

**NOTE:** The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, express or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

RFI.041017.021418