



BLACK FIRE RETARDANT POLY

8 MIL BLACK FIRE RETARDANT POLYETHYLENE SHEETING



PRODUCT DESCRIPTION

8 mil Black Fire Retardant Polyethylene Sheeting contains fire retardant additives and UV inhibitors. This construction film is opaque black with a shelf life of 18 months if stored indoors.

- ▶ Certified: NFPA 701-2004, NFPA 701- 2015 test 1
- ▶ Certified: California Title 19 Fire Retardant Standard
- ▶ Tested and approved for the Boeing BAC5034-2

APPLICATIONS

- ▶ Cargo covers
- ▶ Black-out curtains
- ▶ Covering sensitive shipments
- ▶ Creating barrier walls
- ▶ Temporary privacy curtain
- ▶ Equipment protection
- ▶ Commercial renovation
- ▶ Covering any surface requiring fire retardant film

PRODUCT USE

8 mil Black Fire Retardant Polyethylene Sheeting creates excellent protection and privacy for many types of construction jobs. It's easy to tape in place; easy to cut and size around permanent objects and protects against spill and moisture.

SIZE AND PACKAGING

CB85FR 5' x 500'

CB824FR 24' x 100'

PROPERTIES	TEST DIRECTION	TYPICAL VALUES	UNITS
Tensile Elongation	Machine Direction	525	%
Tensile Elongation	Transverse Direction	650	%
Tensile Strength	Machine Direction	2500	psi
Tensile Strength	Transverse Direction	2300	psi
Elmendorf Tear Strength	Machine Direction	1.25	lbf
Elmendorf Tear Strength	Transverse Direction	2.5	lbf
Flame Spread	ASTME84	PASS	
Smoke Density	ASTME84	PASS	
Fire Retardancy	NFPA 701	PASS	

NOTE: This product is not intended for use under the BAC5034-2. The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, express or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use. Contact Americover for more information.

OE.060717.04082025