



CARPET COVER

3 MIL SELF-ADHESIVE CARPET COVER



PRODUCT DESCRIPTION

This carpet protection film is amazingly strong, durable, puncture and tear resistant. High tech, water based adhesive system has major benefits over solvent-based systems in that it won't discolor or dye the carpets, and it has a clean release for easy removal without adhesive transfer.

This film outperforms similar LDPE based products. It is reverse wound on the roll for fast and easy installation. It removes without adhesive transfer, and will not discolor dye carpets. Americover's carpet cover is designed for jobs, events, or projects up to 45 days per application. Made 100% in the U.S.A.

APPLICATIONS

- ▶ Model Homes
- ▶ Moving
- ▶ Trade shows
- ▶ Exhibitions
- ▶ Remodeling
- ▶ Dust Control
- ▶ High traffic carpet protection
- ▶ Maintenance & repair

PRODUCT USE

Americover recommends that all products be stored and applied indoors at room temperature 60°- 80° F (16°-17° C) and that relative humidity levels be kept between 30% - 70%. All products should be rotated so the "first-in,first-out" inventory method is utilized. For best results products should be applied to a clean, dry surface. It is best for the purchaser to test the suitability of our products under their unique conditions.

SIZE AND PACKAGING

WIDTHS	LENGTHS
24", 36"	200'
36", 48"	500'

PROPERTIES	TEST METHOD	VALUES
Film Backing		Linear Low Density Polyethylene (LLDPE)
Gauge	ASTM D3652	3 mil (0.003")
Tensile Strength	ASTM D882	5620 psi
Elongation at Break	ASTM D882	860% (md)
Adhesion (oz/inch at 180°)	Modified PSTC #101	30.0
Adhesive Color		Water Clear

NOTE: The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, express or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

5G.060717.021318