



# 2-SIDED CLEAR TAPE

CLEAR DOUBLE SIDED SEAMING TAPE



## PRODUCT DESCRIPTION

2-Sided Clear Seaming Tape is a low-stretch core film coated on both sides with a 10 mil, transparent, synthetic rubber adhesive. Each roll is equipped with a coated paper release liner to make installation quicker and easier.

## APPLICATIONS

- ▶ Overlapping Vapor Barriers and Vapor Retarders
- ▶ Sealing Lapped sections of covers
- ▶ Greenhouse Repairs
- ▶ Seaming Covers

## PRODUCT USE

The tape will not adhere to dirty or wet surfaces. The application area should be completely cleaned and dry. Accumulations of dust should also be removed to insure a secure seam. Optimum adhesion occurs when the application surface is above 50-60°F. In order to obtain a bond at lower temperatures, external heat may be required. Extra care should be taken when attempting to install tape at temperatures below 32°F.

## SIZE AND PACKAGING

Sold in individual rolls of 1.5" x 300'.

PROPERTIES	IMPERIAL VALUES	METRIC VALUES
Overall Thickness	15.9 mil	.3975 mm
Adhesive and Carrier Thickness	12.7 mil	.3175 mm
Overall Width	1.75 in.	44.4 mm
Adhesive Width	1.50 in.	38.1 mm
Roll Length	300 ft	91.4 m
Roll Weight	3.75 lbs	1.75 kg
180° Peel Adhesion	150 oz/in	1.64 n/mm
Application Temperature Range	45° F - 105° F	7° C - 40.6° C
Operating Temperature Range	0° F - 140° F	-17.7° C - 60° C

\* Values obtained when using Polypropylene plates.

**NOTE:** To the best of our knowledge, unless otherwise stated, these are typical property values and are intended as guides only, not as specification limits. Chemical resistance, odor transmission, longevity as well as other performance criteria is not implied or given and actual testing must be performed for applicability in specific applications and/or conditions. AMERICOVER, INC. MAKES NO WARRANTIES AS TO THE FITNESS FOR A SPECIFIC USE OR MERCHANTABILITY OF PRODUCTS REFERRED TO, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability for resulting loss or damage. Limited Warranty available at [www.Americover.com](http://www.Americover.com)

RFI.030115.100118