



PRO CRAWL BARRIER™

10 MIL CLASS 1 VAPOR BARRIER



PRODUCT DESCRIPTION

PRO Crawl Barrier is a high performance multi-layer extruded vapor barrier specifically designed to ensure low permeability to protect the building fabric from moisture vapor damage. PCB is manufactured with virgin polyolefin based resins to produce high tensile strength and superior puncture resistance.

PRO Crawl Barrier is a class 1 vapor retarder.

APPLICATIONS

- ▶ Crawl Space Encapsulation
- ▶ Vapor Barrier
- ▶ Underslab Vapor Barrier
- ▶ Wall Vapor Barrier

PRODUCT USE

When properly installed, PRO Crawl Barrier is designed to suppress the transmission of water vapor, which prevents moisture damage and reduces mold, mildew and fungus growth.

SIZE AND PACKAGING

Roll Size: 10' x 100' with a 32" core for low cost shipping

| PROPERTIES | TEST DIRECTION/TEST METHOD | VALUES |
|--------------------------|----------------------------|--------------|
| Tensile Strength | ASTM E 154 | 61 lbs |
| Puncture Resistance | ASTM D 1709 , Method B | 3210 grams |
| Water Vapor Transmission | ASTM F 1249 | 0.0228 perms |
| Chemical Resistance | ASTM 154 | unaffected |
| Roll Dimensions | - | 10' x 100' |
| Roll Weight | - | 56 |

PRO Crawl Barrier Exceeds ASTM E 1745 Class A, B, & C

The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, express or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

T.000000.073018